

# Filter Cartridge DC-644PLF5/1



Product codes: Product attributes:

Reference: PC214-00279 EAN13: -UPC: -

# **Product description:**

The Velcon Permanent Support Tube Kits are designed for use with either the Velcon "DC" disposable cartridges or Facet CIF Series cartridges of appropriate length.

#### **FEATURES**

- Large Surface Area allows high flow rate with low initial pressure drop and maximum contaminant holding capacity
- Resin Impregnated Media maintains strength, resists effects of water and heat
- Aluminum Components resists corrosion from most fluids
- Corrugated Media prevents pleat pinch-off, assuring all filtration media is utilized
- Buna-N Gaskets the best general gasket material available assures positive seal in most fluids
- Thermoset Adhesive Bonding Material durable endcap-to-media bond prevents internal bypassing 98% Filtration Efficiency with Micron Ratings 1 - 5



#### **APPLICATIONS**

Velcon pleated paper media cartridges are suitable for a broad range of polar and non-polar fluids. Recommended for applications where the contaminant is granular (non-colloidal), allowing maximum utilization of the high surface area.

### Suitable for:

- All hydro-carbon fuels
- Toluol
- Cutting oils
- Lube oils
- Glycols
- Synthetic oils
- greasing fluids
- Ethyl alcohol
- Insulating oils
- Hydraulic oils
- Water emulsion coolants
- Naphtha

## **Technical Specifications**

- Micron Rating (µm):5
- Application:Industrial
- Length (inch):44
- Outside Diameter (inch):6
- pH Range:Continuous Operation: 5-9
- Maximum Operating Temperature:200 °F, 93.3 °C
- Application:Industrial
- Filter Type:Disposable
- Filter Construction:Coreless
- Brand:Velcon