

# Filter Cartridge CDF-205P



## Product codes:

Reference:  
PC214-00282  
EAN13: -  
UPC: -

## Product attributes:

## Product description:

### Features

- CDF® P SERIES are qualified to EI 1583 Sixth Edition specification for Aviation Fuel Filter Monitors.
- IMPROVED SALT WATER PERFORMANCE
- CONDUCTIVE END CAPS and adhesive to reduce static charge within the vessel.
- O-RING SEAL minimizes the possibility of bypassing contaminated fuel at differential pressures up to 175 psi.
- RUGGED CONSTRUCTION collapse strength exceeds 175 psi differential pressure.

The Velcon CDF® P Series cartridges are designed to provide superior performance and reliability in standard fuel monitor housings through a unique, patented combination of media that absorbs water, filters solids that may be present in the fuel and provides for reduced static charge.

The cartridge has injection molded endcaps that are bonded to the media and an O-ring seal on

the outlet end. This minimizes the possibility of bypassing contaminated fuel or transmission of water downstream at low flow rates.

- 175 psid (12 bar) collapse strength
- 0.5 micron rating
- 160°F maximum operating temp.
- Recommended changeout differential pressure = 25 psid
- Typical water holding capacity for CDF-230P is 120 ml.