

Filter Cartridge ACO-51301R

**Product codes:**

Reference:
PC214-00290
EAN13: -
UPC: -

Product attributes:**Product description:**

Manufacturer: Parker Hannifin

Filtration rate: 0.5 Micron

Service: Fuel

Size: 1-7/8" ID x 5,5/8" OD x 12,1/4" L.

Filter Control Cartridge

Cartridge Type; Size 1-1/32" ID x 2-5/8" OD x 9-3/4" L; 0.5 Micron Filter; Fuel Service; Temperature Rating 250 degrees F; Pressure Rating 75 PSI (collapse); Flow Rate 50 GPM; Efficiency 98 percent; Used on VF-61 Housing; Aviation Application; Applicable Standard EI 1583

Features/Benefits

Removal of free water and emulsified water at less than 5 PPM; splash protection; pressure increase signals the need to change the cartridge; use with an existing filter housing; improved configuration to help reduce the risk of downstream super absorbent polymer (SAP) migration

Series/model information

Aquacon® patented filter cartridges have a unique high capacity internal absorbent medium that removes all free and emulsified hydrocarbon water down to less than 5 ppm in the effluent. The absorbed water is chemically locked into this medium. When a cartridge reaches its water holding capacity, its accordion pleats swell and cause an increase in differential pressure which signals the operator to change the cartridge.