

# Filter Cartridge AC-718P3

**Product codes:****Product attributes:**

Reference:  
PC214-00296  
EAN13: -  
UPC: -

**Product description:**

Parker Velcon AC Aquacon Water Absorbing Filter Cartridge, 1-7/8 in ID x 5-5/8 in OD x 12-1/8 in len, pleated 5 micron media with inner layers of water absorbing media, change at 25 psid, Buna-N, for motor gasoline or insulating oil use.

Aquacon Cartridges have a patented\* construction for removing dirt and water from hydrocarbon and other oils as well as gases. The outer media layer filters out silt, rust and other particulate contaminants. The inner layers absorb water and chemically bond it so that no water will release downstream. When the Aquacon Cartridge reaches its water holding limit, the media swells shut and the differential pressure rapidly increases. This signals the operator that the cartridge must be changed.

- Removes free and emulsified water to less than 2 ppm
- Differential pressure increase alerts operator to change cartridges
- Effectively filters silt and other particulates
- No media migration or “linting”
- Easy to install and remove

- Does not affect oil additives
- Fits standard filter housings
- Manufacturer: Parker Hannifin
- **I.D.:** 1-7/8 in
- **Length:** 12-1/8 in.
- **Micron Rating:** 5
- **O.D.:** 5-5/8 in